MoodleScript: REMOVE BLOCK

MoodleScript Script Engine

Effect

Removes blocks from a course.

Syntax

```
REMOVE BLOCK <blockname> FROM <courseidentifier>
```

```
REMOVE BLOCK <blockidentifier> (todo)
```

```
REMOVE BLOCK <blockname> FROM <courseidentifier> HAVING
location: <location>
position: <position>
```

Examples

```
REMOVE BLOCK course_recycle FROM current HAVING
```

```
REMOVE BLOCK html FROM idnumber:"C203" HAVING
location: side-pre
position: last
```

Specific attributes

- **blockname**: must be an unprefixed block name: 'course_recycle' or 'dashboard' or 'configurable_report' for example.
- **blockidentifier**: a block identifier. (*)
- **courseidentifier**: a “course” object identifier. For example: idnumber:<courseidnum>
- **location**: a block region identifier, for example: side-pre or side-post. This may depend on the theme. The *default* value should add the block to the default block region (where the add-block widget is located in the interface).
- **position**: a position (numeric integer) or the keywords *first* or *last*.

Default values

- **location** : side-post
- **position** : 0

Other defaults

These default values cannot be altered by the MoodleScript syntax in the current version.

- **showinsubcontext** : 0
- **pagetypepattern** : course-view-*

Notes

(*) This assumes the block identifiers provided by the installation of certain third-party plugins are in place.

Back to the language index - Back to the component index

From:
https://docsen.activeprolearn.com/ - **Documentation Moodle ActiveProLearn**

Permanent link:
https://docsen.activeprolearn.com/doku.php?id=local:moodlescript:language:removeblock

Last update: **2026/11/13 21:59**