

# Local Shop : General configuration

## Introduction

The shop must be generally configured with vendor information in order to operate.

Path: Site administration/plugins/local plugins/shop

The configuration involves four set sections and a certain amount of variable sections depending on the number of payment plug-ins installed.

## Global settings

- **Default front office navigation:** This parameter indicates the sequencing order of front office screens. The shop stores all pre-purchase data during a session. This data can be in a different order according to the business or the wishes of the operator.

⚠ Be careful: navigation sequence implicates all front office screens. Some combinations can generate shop malfunctions, such as, for example, attempting to display an invoice before a payment. There are consequently certain rules that need to be followed, notably:

- Differentiate between “pre-payment” screens and “after payment” screens
- Provide the invoice after payment

### **Pre-payment steps:**

- **shop** : establish the cart
- **purchaserequ** : collect product parameters
- **users** : enter information on seats
- **customer** : collect customer information / existing customer login
- **order** : order summary

### **Payment steps (or steps after payment):**

- **payment** : payment or redirect to a payment interface
- **produce** : digital production of purchased products
- **invoice** : presentation of invoice or pro forma invoice
- **Default currency** : Selects the currency given for the shop.

⚠ Note : The multi-currency shop operation is planned, but still requires some finalisation. (Utilisation de plusieurs devises dans la même instance de catalogue.)

- **Test mode** : Si ce mode est activé, alors toutes les interfaces de paiement activées le sont sur les paramètres de bac à sable des différents partenaires de paiement. De plus l'usage de la phase de paiement est interdite aux personnes non connectées et non administrateur. Cependant, les transactions effectuées en mode test généreront des enregistrements effectifs de factures et de produits. Il peut être nécessaire de procéder à une réinitialisation des transactions avant la mise en production effective de la boutique.

- If this mode is enabled, then all payment interfaces are enabled based on the sandbox parameters of the different payment partners. Furthermore, persons who are not logged in or who are not administrators are prohibited from payment phase use. Transactions made in test mode however will generate actual records of invoices and products. Transactions might have to be reinitialised before the shop is actually in production.
- **Test lock override** : Si ce mode est activé, alors le verrouillage des achats en mode test est levé, pour aller au bout d'une transaction.
- **Max items** : Determine the max. size of list displays in the back office.
- **Hide products if not available** : Défaut : No. If enabled, non available products (for availability check reasons, but yet published for sale) will not be shown at all on front. If disabled, they still appear but shadowed and without the ordering button.

**Global settings**

Default front office navigation  
local\_shop | defaultnavsteps  
  
Default: shop.purchasesequ.users.customer.order.payment.produce.invoice  
Some office owners may reorder the steps in the front process. Keep in mind some orders might NOT work correctly, i.e. trying to get payment before thoc cart and customer are defined.

Default Currency  
local\_shop | defaultcurrency  
  
Default: Euro  
Currency suffix

Test mode  
local\_shop | test  
☒  
Default: No  
Enables the mode test for the payments

Test lock override  
local\_shop | testoverride  
☐  
Default: No  
Overrides test lock on purchase to test simulated external users

Max items  
local\_shop | maxitemsperpage  
  
Default: Empty  
Max items per page

Hide products if not available  
local\_shop | hideproductswhennotavailable  
☐  
Default: No  
If enabled, non available products (for availability check reasons, but yet published for sale) will not be shown at all on front. If disabled, they still appear but shadowed and without the ordering button.

## Discount settings

The Moodle shop handles a three-tiered discount system. A discount can only be attributed by logged in users based on certain capabilities at system level.

The discount is applied to the order total and is triggered by a sales threshold. A customer can benefit from a more or less significant discount according to the level of discount they earn by right, but the trigger threshold remains unique. (You cannot tier up different automatic discounts according to cart amount).

To modulate prices according to local quantities with a product, view the settings for a single product. Only one discount threshold can be applied at a time (discounts are therefore not cumulative).

- **Discount threshold:** A threshold that triggers the effectivity of the discount. Users must have **local/shop:discountagreed** capability to benefit from it.
- **Discount rate:** Is expressed as a % of total order amount. A discount rate applied on the overall amount. May be applied unconditionally if customer has the local/shop:discountagreed capability on
- **Second discount rate:** This rate is applied to logged in users : A discount rate applied when customer has the local/shop:seconddiscountagreed capability on You can, for example, create a

site role with this capability and have this role attributed via a badge to identify preferred customers.

- **Third discount rate:** Likewise, a third discount rate can be triggered for **local/shop:thirddiscountagreed** capability.

**Discount settings**

Discount Threshold <small>local_shop   discountthreshold</small>	<input type="text" value="0"/>	Default: 0 A threshold that triggers the effectivity of the discount
Discount Rate <small>local_shop   discountrate</small>	<input type="text" value="0"/>	Default: 0 A discount rate applied on the overall amount. May be applied inconditionally if customer has the local/shop:discountagreed capability on
Discount Rate 2 <small>local_shop   discountrate2</small>	<input type="text" value="0"/>	Default: 0 A discount rate applied when customer has the local/shop:seconddiscountagreed capability on
Discount Rate 3 <small>local_shop   discountrate3</small>	<input type="text" value="0"/>	Default: 0 A discount rate applied when customer has the local/shop:thirddiscountagreed capability on

## Information about vendor's identity

- Seller name: Seller name displayed on screens.
- Seller address : physical adress.
- Seller zip code: Zip code displayed for the seller identity.
- Seller city : City of the merchant.
- Seller country: Country displayed.
- Seller email: Direct email.
- Mail adress support: Mail address of the sales customer support team.
- Phone support number: Phone number of the sales customer support team.

Lastly, accounting information is used to display any different data on documents produced (purchase orders, pro forma invoices, invoices, etc.)

- Seller Registrar ID: The official company registrar ID of the seller.
- Seller Billing address: The accountance location of the merchant.
- Seller Billing Zip Code: Zip code of the accountant service.
- Seller Billing city : City of accountance service.
- Seller Billing country: Country of accountant service.
- Seller Logo : the logo that will be printed on invoices and orders.

Information about vendor's identity

Seller name

local\_shop | sellername

ActiveProLearn

Default: Empty

The official name of the vendor

Seller Address (physical)

local\_shop | selleraddress

Rond Point Benjamin Franklin

Default: Empty

The address (postal) of the merchant

Seller Zip Code

local\_shop | sellerzip

34000

Default: Empty

Zip code for the seller identity

Seller City

local\_shop | sellercity

Montpellier

Default: Empty

City of the merchant

Seller Country

local\_shop | sellercountry

France

Default: Empty

Country of the merchant

Seller Email

local\_shop | sellermail

ventes@activeprolearn.com

Default: Empty

Mail address of the merchant

Mail support address

local\_shop | sellermailsupport

support@activeprolearn.com

Default: Empty

Mail address of the sales customer support team

Phone support number

local\_shop | sellerphonesupport

Default: Empty

Phone number of the sales customer support team

Seller Registrar ID

local\_shop | sellerid

Siret 801 675 299 00011

Default: Empty

The official company registrar ID of the seller

Seller Billing Address

local\_shop | sellerbillingaddress

Rond Point Benjamin Franklin

Default: Empty

The accountance location of the merchant

Seller Billing Zip Code

local\_shop | sellerbillingzip

34000

Default: Empty

Zip code of the accountant service

Seller Billing City

local\_shop | sellerbillingcity

MONTPELLIER

Default: Empty

City of accountance service

Seller Billing Country

local\_shop | sellerbillingcountry

FRANCE

Default: Empty

Country of accountant service

Seller logo

local\_shop | sellerlogo

Maximum size for new files: Unlimited, maximum attachments: 1

Files

ActiveProLearn

logo-APL-gd.png

Default: Empty

the logo that will be printed on invoices and orders

Settings related to payment plug-ins

Each installed payment plug-in can add a set of parameters dedicated to this plug-in functioning. Here

https://docsen.activeprolearn.com/

Printed on 2025/06/09 04:20

are some examples.

## Mercanet configuration option

The Mercanet interface is the interface used by BNP and banks in that same group.

### Mercanet configuration options

Mercanet Merchant ID  
local\_shop | mercanet\_merchant\_id

Default: Empty  
Merchant ID. Provided by Mercanet.

Country code  
local\_shop | mercanet\_country

France ▼

Mercanet country

Generate the Pathfile file

Currency code  
local\_shop | mercanet\_currency\_code

Euros ▼

Currency code

Processor type  
local\_shop | mercanet\_processor\_type

32 bits ▼

Determines API Processor type to be used (Linux versions)

## Ogone configuration option

Ogone (now Ingénico), is a multi-bank payment intermediary that can centralise payments received via a unique interface for several different banking systems.

### Ogone/Ingenico configuration options

Ogone/Ingenico Merchant Identifier  
local\_shop | ogone\_id

Default: Empty  
Ogone/Ingenico Merchant Identifier

Secret glue for gateway input  
local\_shop | ogone\_secret\_in

Default: Empty  
This glue is used to secure the transfer of your merchant data to the ogone gateway. It needs to be identical to the secret you have setup in the ogone account backoffice.

Secret glue for gateway output  
local\_shop | ogone\_secret\_out

Default: Empty  
This glue is used to check the answers of the ogone gateway. It needs to be identical to the secret you have setup in the ogone account backoffice.

Multiple Shop diverter info  
local\_shop | ogone\_paramvar

Default: Empty  
This is to be used in case you have multiple shops hosted on the same facility (See Ingenico/Ogone Integration Documentation)

Logo URL  
local\_shop | ogone\_logourl

Default: Empty  
An URL to your logo for the remote payment page. (must be an HTTPS url as ogone payment service is secured)

## Paypal

When using test mode, you will send all purchases to the Paypal sandbox. Paypal sandbox do NOT

automate the IPN process (asynchronous return to merchant site) and you will have to simulate it using the Paypal IPN Simulator. The IPN end point of this site is : [http://ma.formation-enligne.com/local/shop/paymodes/paypal/paypal\\_ipn.php](http://ma.formation-enligne.com/local/shop/paymodes/paypal/paypal_ipn.php).

Paypal configuration options

When using test mode, you will send all purchases to the Paypal sandbox. Paypal sandbox do NOT automate the IPN process (asynchronous return to merchant site) and you will have to simulate it using the Paypal IPN Simulator. The IPN end point of this site is : [http://ma.formation-enligne.com/local/shop/paymodes/paypal/paypal\\_ipn.php](http://ma.formation-enligne.com/local/shop/paymodes/paypal/paypal_ipn.php).

Paypal seller test account (paypal sandbox)

vent@activeprolearn.com

local\_shop | paypal\_seller\_test\_name

Default: Empty  
The account id of the reseller

Sales Service (test mode)

Sandbox Paypal APL

local\_shop | paypal\_seller\_test\_name

Default: Empty  
An arbitrary label that allows sorting transactions against multiple selling services

Paypal seller account

vent@activeprolearn.com

local\_shop | paypal\_seller\_name

Default: Empty  
The account id of the reseller

Sales Service

Ventes Paypal APL

local\_shop | paypal\_seller\_name

Default: Empty  
An arbitrary label that allows sorting transactions against multiple selling services

System Pay PLUS

System Pay PLUS, developed by ATOS, is the payment system used by Caisse d'Epargne, the Banques Populaires, and banks in that group.

System Pay PLUS Settings

Service URL

https://payzen.societegenerale.eu

local\_shop | systempay\_service\_url

Default: Empty  
Url for Payment Transaction Server

Merchant ID

9522

local\_shop | systempay\_merchant\_id

Default: Empty  
This is the ID of the merchant service provided in your backoffice interface

Test certificate

32411

local\_shop | systempay\_test\_certificate

Default: Empty  
The certificate key to encode test submissions

Prod certificate

7911999506

local\_shop | systempay\_prod\_certificate

Default: Empty  
The certificate key to encode production submissions

Use 3D Secure service

☒

local\_shop | systempay\_use\_3dsecure

Default: No  
3D Secure is an option to the merchant payment contract that will callback the customer for a confirmation code.

Bank brand

Payzen / Société Générale

local\_shop | systempay\_bank

Default: Caisse d'Epargne

Country

France

local\_shop | systempay\_country

Country

Currency Code

Euro

local\_shop | systempay\_currency\_code

Currency Code

Use local time

☒

local\_shop | systempay\_use\_localtime

Default: Yes  
Use local time for transactions, or UTC/GMT time if not checked.

## Notifications

- **Pre sales notifications** : Enable or disable the order input notification.

### Notifications

Pre sales notifications

☒

local\_shop | presalenotification

Default: Yes

Enable or disable the order input notification

## Reseller banking information

### Introduction

The vendor's banking information is used for offline payment procedures to provide bank details for interbank transfers or for issuing cheques. This information is found in your bank documentation.

- Bank name :Bank company name
- Bank code :Bank code of the merchant
- Bank office: Agency code
- Bank Account : Agency code
- Bank account key :Account key of the merchant
- IBAN : The IBAN number of the merchant
- BIC : BIC identification code of the merchant's bank
- VAT European Intracommunautary:European VAT number



Reseller banking information

Banking local_shop   banking	<div>SOCIE [REDACTED] RALE</div> <div>Default: Empty Bank company name</div>
Bank code local_shop   bankcode	<div>300 [REDACTED]</div> <div>Default: Empty Bank code of the merchant</div>
Bank Office local_shop   bankoffice	<div>01 [REDACTED]</div> <div>Default: Empty Agency code</div>
Bank Account local_shop   bankaccount	<div>00027004001</div> <div>Default: Empty Agency code</div>
Bank Account Key local_shop   bankaccountkey	<div>9 [REDACTED]</div> <div>Default: Empty Account key of the merchant</div>
IBAN local_shop   iban	<div>FR [REDACTED] 195</div> <div>Default: Empty The IBAN number of the merchant</div>
BIC local_shop   bic	<div>SO [REDACTED] PP</div> <div>Default: Empty BIC identification code of the merchant's bank</div>
VAT European Intracommunautary local_shop   tva europe	<div></div> <div>Default: Empty European VAT number</div>

Appareance

Introdution

Cette section permet de gérer l'apparence des produits en front-office



## Appearance

Thumb height  
local\_shop | productimageheight

Default: 150  
Product thumb height (px)

Thumb width  
local\_shop | productimagewidth

Default: 150  
Product thumb width (px)

Thumb right margin  
local\_shop | productimagemargin

Default: 40  
Product thumb right margin (px)

Element thumb height  
local\_shop | elementimageheight

Default: 80  
Product subelement thumb height (px)

Element thumb width  
local\_shop | elementimagewidth

Default: 80  
Product subelement thumb width (px)

Element thumb right margin  
local\_shop | elementimagemargin

Default: 25  
Product subelement thumb right margin (px)

## Experimental

These features are enabled but still subject to change.

- **Use shipping :** Default: No: If enabled, delivery charges are handled.
- **Use sales delegation:** Default: No: If enabled, users can own products and sell them on their own behalf : The Moodle shop is also designed to be a marketplace for course authors. This feature will only be available in the extended version of the shop (PRO). The sales delegation provides that the catalogue products can belong to delegate seller accounts (generally associated with the course author) so that the platform can manage sales on behalf of the author. Representatives will have access to a portion of the back office in order to monitor sales management.
- **Use master/slave catalogues:** Default: No. If enabled, master/slave catalogues are handled.
- **Use renewable products:** Default: No: If enabled, renewable products are handled.

## Experimental features

- |  |  |
|--|--|
| Uses shipping<br>local_shop   useinshipping                  | <input checked="" type="checkbox"/><br>Default: No<br>Enables the shipping costs engine                                |
| Use sales delegation<br>local_shop   usedelegation           | <input type="checkbox"/><br>Default: No<br>If enabled, some users may get ownership of products and sales in the shop. |
| Uses master/slave catalogs<br>local_shop   useslavecatalogs  | <input checked="" type="checkbox"/><br>Default: No<br>Uses master/slave catalogs                                       |
| Uses renewable products<br>local_shop   userenewableproducts | <input checked="" type="checkbox"/><br>Default: No<br>Uses renewable products  |

## Plugin distribution

- |  |  |
|--|--|
| Emulate community version<br>report_trainingessions   emulatecommunity | <input type="checkbox"/><br>Default: No<br>If enabled, the plugin will behave as the public community version. This might loose features ! |
|--|--|

## Credits

- Valéry Frémaux (valery@activeprolearn.com) Conception - Developments - Documentation
- Florence Labord (florence@activeprolearn.com) Revue Fonctionnelle - Tests - Documentation

[back to local shop composant](#) - [Back to catalogue](#)

From:  
<https://docsen.activeprolearn.com/> - **Moodle ActiveProLearn Documentation**

Permanent link:  
<https://docsen.activeprolearn.com/doku.php?id=local:shop:globalconfig&rev=1518620389>

Last update: **2024/04/04 15:50**

