Group and grouping synchronisation file

Synchronisation by CSV file

Group creation file format

Field	Value	Default
courseid(*)	primary identifier of the course	
name(*)	group name	-
idnumber	String	-
groupid	group id (in case of modification)[1]	-
selfgrouping	0 or 1	If 1, creates a grouping with the same name as the group
grouping	int	Grouping Id
description	String	-

- (*) Mandatory fields
- (1) According to the tool setting. If the group identifier is not qualified enough, then the `courseid` value is combined with it. The `groupid` column is only to be used when renaming groups. This identifier takes precedence over the mandatory `courseid`/`name` combination.

Group population file format

Field	Value	Default
groupid(*)	primary identifier of the course[1]	
userid(*)	user identifier[2]	-
courseid	Course identifier (according to the general setting of the course tool[3]	-
cmd	'add', 'shift', 'del'	'add'

- (*) Mandatory fields
- (1) According to the tool setting
- (2) According to the tool setting
- (3) This column is needed when the primary identifier of the group is its name, because the name is not a fully qualified identifier. Several groups can have the same local name across different courses.

Back to the component index

From:
https://docsen.activeprolearn.com/ - **Documentation Moodle ActiveProLearn**

Permanent link:
https://docsen.activeprolearn.com/doku.php?id=tool:sync:files:groups

Last update: **2026/11/13 20:37**